



Designed and Developed in Singapore



Specifications

Input

Type XLR- $\frac{1}{4}$ " locking combo jack

Output

Type $\frac{1}{8}$ " TRS, stereo

Impedance 0.5 Ω

Max. output 2 x 100 mW @ 16 Ω

Power

Batteries 2 x AAA (not included)

Battery life ~12 hours

Physical

Dimensions (H x W x D) 33 x 38 x 132 mm
(1.3 x 1.5 x 5.2")

Weight 140 g (0.3 lbs)

1 BATTERY SLOTS

Battery Slots allow the unit to be powered by a pair of AAA batteries. Observe the correct polarity when inserting new batteries.

2 INPUT JACK

Input Jack accepts XLR or $\frac{1}{4}$ " male plugs for connection of a personal monitor mix. Press the release tab to disconnect the cable.

3 BELT CLIP

Belt Clip attaches to a belt or pant waistline for hands-free use.

4 MONO / STEREO

Mono / Stereo switch should be set to Mono when used with a mixer's aux send or any other mono source, and set to stereo when connected to a headphone output or other stereo source.

5 VOLUME KNOB

Volume Knob adjusts the output level and powers the unit off when turned fully counterclockwise. The adjacent LED will light when the power is on.

6 HEADPHONE

Headphone output allows connection of a $\frac{1}{8}$ " stereo mini jack.